





Unified Grobgewinde UNC ASME B1.1
UNC coarse thread ASME B1.1

Blauer Ring Mit Gerade Spiralnuten 48°
Blue Ring Spiral Flutes 48°

HSSV3





Superb-48°- x INOX
H42TLW



DIN 371 d1 ≤ 3/8 unc

DIN 376 d1 ≥ 7/16 unc



Bestell - Nr. - Cat. No.	H42TLW			
Norm - Standard	DIN 371//376			
Schneidstoff - Tool material	HSSV3			
Oberfläche - Surface	TLW			
Toleranz - Tolerance	2BX			
Anschnittform - Chamfer form	C/2-3			

Einsatzgebiet - Application	1.3 - 1.4 - 1.5			
	2.1 - 2.2 - 2.3 - 2.4			

Ød1	TPI	L1	L2	Ød2	a		Identnummer - Code
UNC6	32	56	7	4	3	2,85	H42TLWUNC6-32
UNC8	32	63	7	4,5	3,4	3,5	H42TLWUNC8-32
UNC10	24	70	8	6	4,9	3,9	H42TLWUNC10-24
UNC1/4	20	80	10	7	5,5	5,1	H42TLWUNC1/4-20
UNC5/16	18	90	13	8	6,2	6,6	H42TLWUNC5/16-18
UNC3/8	16	100	15	10	8	8	H42TLWUNC3/8-16
UNC7/16	14	100	15	8	6,2	9,4	H42TLWUNC7/16-14
UNC1/2	13	110	18	9	7	10,8	H42TLWUNC1/2-13
UNC9/16	12	110	20	11	9	12,2	H42TLWUNC9/16-12
UNC5/8	11	110	20	12	9	13,5	H42TLWUNC5/8-11
UNC3/4	10	125	25	14	11	16,5	H42TLWUNC3/4-10
UNC7/8	9	140	25	18	14,5	19,5	H42TLWUNC7/8-9
UNC1"	8	160	30	18	14,5	22,25	H42TLWUNC1-8